

PATENT APPLICATION

TITLE: METHOD OF ASSEMBLING PERSONAL CARE ABSORBENT ARTICLE

By: Harold Norbert Heller
Residing at: 1416 Maria Lane
Menasha, WI 54952
Citizenship: USA

By: Donald Joseph Sanders
Residing at: 8348 Pine Cone Circle
Larsen, WI 54947
Citizenship: USA

"Express Mail" mailing number

EL 766079861 US

Date of Deposit April 13, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to:

Box Patent Application, Assistant Commissioner for Patents, Washington, D.C. 20231.

Elisha St. Croix

(Typed or printed name of person mailing paper or fee)

Elisha St. Croix 04/13/01
(Signature of person mailing paper or fee) (Date)

JGS/TDW

BACKGROUND OF THE INVENTION

This invention relates to apparatus and methods for assembly of personal care absorbent articles, as well as to such personal care absorbent articles. More specifically, this invention relates to methods of assembly and apparatus for assembling especially re-fastenable personal care absorbent articles wherein the methods of the invention attenuate certain counterproductive aspects of conventional manufacture of such personal care absorbent articles. While embodiments of the present invention are described herein in terms of personal care absorbent articles such as pull-on pants or adult incontinence briefs, the invention includes, and is equally applicable to a wide variety of articles fabricated in web formats, such products as infant diapers, training pants, and the like.

In conventional methods for fabricating disposable personal care articles, it is known to fold over a web or webs of a stream of workpieces at a first, relatively earlier stage in the manufacturing process to form a stream of individual personal care article precursors.

Yet other conventional methods reflect adjacent personal care article precursors being attached to one another along the stream of workpieces by e.g. front portion material, wherein the front portion material is cut out or apart to separate such articles at the end of the process. Associated with the second, relatively later stage of conventional manufacturing processes is the excision and removal of significant cut-out portions affiliated with e.g. front portion materials, leg cut-out regions, and/or trim between side seams of adjacent articles, from the web or webs resulting in significant material waste attributable to such inefficient conventional manufacturing processes.

A need exists for improved methods for production of personal care absorbent articles wherein the methods are effective to attenuate waste in a manufacturing process as well as to reduce cost inevitably associated with inefficiency of such manufacturing process.

Thus, it is an object of this invention to provide methods for production of personal care absorbent articles which methods maintain unsegmented streams of workpieces, without severing respective front portions and rear portions from a respective web sausage, until relatively late in the process, with respect to

conventional methods, thereby enabling manufacturers of personal care articles to integrate personal care article components into the web sausage in the context of an entire stream of workpieces rather than individual workpiece precursors.

5 It is another object of this invention to provide methods for the production of personal care absorbent articles which methods improve control and stability of the stream of workpieces as such stream of workpieces is affected along the manufacturing line.

10 It is a further object to provide manufacturing processes which reduce cost to manufacturers by enabling a manufacturer to minimizing on-line material waste associated with the manufacturing process.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207

SUMMARY OF THE DISCLOSURE

In a first family of embodiments, the invention comprehends a method of manufacturing personal care absorbent articles in a format which includes defining a stream of workpieces connected to each other along a web sausage having an indefinite length. Each of respective such personal care articles has a front portion including a front edge, a rear portion, and a crotch portion between the front portion and the rear portion. The method comprises, for a given workpiece in the web sausage, defining the front portion, the rear portion, and the crotch portion, and defining a fastening area in the front portion for receiving fastener material thereon. The method also comprises forming first and second fault lines in the workpiece on opposing sides of the fastening area, the first and second fault lines being oriented in directions generally extending between the front portion and the rear portion when a blank of the workpiece is laid out flat. Additionally, the method comprises applying fastener material over the respective first and second fault lines. The fastener material, as applied, extends across, and thus bridges, the respective fault lines. The fastener material is releasably secured to the fastening area, is non-releasably secured to the front portion outwardly of the respective fault lines, and is unsecured to the front portion between the fastening area and the fault lines. The method also comprises separating individual such workpieces from the web sausage as such personal care articles.

In preferred embodiments, the method includes cutting leg cut-outs in the web sausage between the respective workpiece and adjacent workpieces, and correspondingly cutting into the respective fault lines in so cutting the leg cut-outs.

In preferred embodiments, each of the first and second fault lines is formed as a cut line of one or more elongate cuts and minor, if any, web connections therebetween, with uncut web portions at opposing ends of the cut line, sufficiently strong, in combination, to support integrity of the front portion across the fault lines. The cutting into the fault lines in cutting the leg cut-outs is effective to remove the uncut web portions adjacent the leg cut-outs and to thereby communicate with the cut line. The method further includes separating material along a front edge of the workpiece thereby to form the front edge of the personal care article and to separate the substantial uncut web portion at the front edge and thereby further communicate with

the cut line, such that the fastener material provides primary support of the front portion across the fault lines.

In some embodiments, the method includes forming each of the first and second fault lines as a cut line of one or more elongate cuts and minor, if any, web connections therebetween, with substantial uncut web portions at opposing ends of the fault line, wherein the cutting into the fault line at the cutting of the leg cut-out comprehends removing the entirety of the uncut web portion at the respective end of the fault line.

In other embodiments, the method includes forming each of the first and second fault lines as a cut line of one or more elongate cuts and minor, if any, web connections therebetween, with relatively shorter-length perforation cuts and corresponding effective uncut web support connections between such perforation cuts at opposing ends of the one or more elongate cuts.

In preferred embodiments, the method further includes separating material along a front edge of the workpiece thereby forming the front edge of the personal care article and thus removing the effective support connections at the front edge, such that the fastener material provides primary support of the front portion across the fault lines.

In yet other embodiments, the method includes forming each of the first and second fault lines as a line of relatively uniformly formed and uniformly spaced perforations.

Some embodiments can include cutting leg cut-outs between the respective workpiece and adjacent workpieces in the web sausage, and correspondingly removing first perforated end portions of the respective fault lines in so cutting the leg cut-outs, and separating material along a front edge of the workpiece and thereby forming the front edge of the personal care article, and correspondingly, separating second perforated end portions of the respective fault lines at the front edge, such that the fastener material provides substantial support of the front portion across the fault lines in combination with support provided by web connections between respective ones of the perforations.

In still other embodiments, the method includes forming each of the first and second fault lines as a line of relatively uniform perforations with relatively short

and uniform uncut web portions between the respective perforations, and relatively longer uncut web portions at opposing ends of the respective line of perforations.

Some embodiments include cutting leg cut-outs between the respective workpiece and adjacent workpieces in the web sausage, and correspondingly removing portions of the respective fault lines in so cutting the leg cut-outs, the removing of the portions of the fault lines in cutting the leg cut-outs being effective to remove uncut web portions adjacent the leg cut-outs and to communicate with the line of perforations. The method can further include separating material along a front edge of the workpiece thereby to form the front edge of the personal care article and separating the substantial uncut web portion at the front edge to thereby further communicate with the line of perforations, such that the fastener material provides substantial support of the front portion across the fault lines.

In even yet other embodiments, the method includes forming the fault lines as pressure lines which are defined by a process of crushing web material which responds to a crushing force, using a dull knife against an anvil roll, and reserving uncrushed web portions at least at opposing ends of the respective pressure lines.

In some embodiments, the method includes employing, as the fastening material, first and second fasteners extending across, and thus bridging, the respective first and second fault lines.

Some embodiments can include the first and second fasteners employing first fastening material effective to interact with second different fastening material in the fastening area.

In preferred embodiments, the method includes fabricating such personal care article using first and second front and rear portion webs, including bringing the rear portion web and the front portion web into facing relationship with each other, and forming side seams connecting the front and rear portion webs to each other, outwardly of such fault lines, thereby to form individual workpiece precursors of such personal care articles, having joined front and rear portions.

In a second family of embodiments, the invention comprehends a method of manufacturing personal care absorbent articles having leg openings on opposing sides of the crotch portion. The method comprises, for a given workpiece, forming first and second fault lines in the workpiece on opposing sides of the fastening area. The first

and second fault lines generally extend from a front edge of the workpiece to the respective leg openings, and the first and second fault lines have centrally located relatively weaker portions, and relatively stronger portions adjacent the leg openings and the front edge. The method also includes applying first and second fasteners over the respective first and second fault lines, releasably securing the first and second fasteners to the fastening area, and non-releasably securing the first and second fasteners to the front portion outwardly of the respective fault lines, as well as maintaining the first and second fasteners unsecured to the front portion between the fastening area and the fault lines. Additionally, the method includes cutting away the relatively stronger portions of the fault lines adjacent the leg openings and adjacent the front edge thereby to form the front edge, such that material of the front portion is precluded from independently supporting the integrity of the front portion across the fault lines. The method also includes separating individual such workpieces from the web sausage as such personal care articles.

In preferred embodiments, the method includes cutting away the relatively stronger portion adjacent the leg openings concurrently with forming at least a portion of the respective leg opening in a workpiece precursor of such personal care article.

In preferred embodiments, the method includes cutting away the relatively stronger portion adjacent the front edge concurrently with forming the front edge in a workpiece precursor of such personal care article.

In a third family of embodiments, the invention comprehends a method of manufacturing personal care absorbent articles having leg openings on opposing sides of the crotch portion and between the front portion and the rear portion. The method comprises drawing a front portion web and a rear portion web in parallel and transversely spaced juxtapositions along an operations path. The method also comprises defining fastening areas in the front portion web, and thereby defining locations in the front portion web for development of respective workpieces in combination with adjoining areas of the rear portion web. Additionally, the method comprises forming first and second fault lines in the front portion web, on opposing sides of the respective fastening areas. The first and second fault lines are oriented in directions generally extending between the front portion web and the rear portion web when the front portion web and the rear portion web are displaced from each other and arranged

in a common relatively flat surface. The first and second fault lines have centrally located relatively weaker portions and relatively stronger end portions adjacent the leg openings and adjacent the front edge of the respective workpiece. Additionally, the method includes applying fastener material over the respective first and second fault lines, the fastener material, as applied, extending across, and thus bridging, the respective fault lines, and being releasably secured to the fastening area, being non-releasably secured to the front portion web outwardly of the respective fault lines, and being unsecured to the front portion web between the fastening area and the fault lines. The method also comprises securing crotch elements to the front portion web and the rear portion web at respective workpiece locations, and thereby defining the respective workpieces and providing transverse direction linking connections between the front portion web and the rear portion web at the respective workpieces. The method further includes cutting away the relatively stronger end portions of the fault lines such that material of the front portions of the resulting personal care articles are precluded from independently supporting integrity of the front portions of the personal care articles across such fault lines. The method further comprises bringing the rear portion web and the front portion web into folded over engaging relationship with each other and forming side seams between the front portion web and the rear portion web outwardly of the fault lines on a respective workpiece, thereby to define individual personal care articles. The method also includes separating individual such personal care articles from the web sausage, thereby to form individual such personal care articles.

In some embodiments, the method further includes separating material along the front portion web thereby to form the front edges of the personal care articles and to separate the substantial uncut web portion at the front edge and to thereby further to communicate with the cut line, such that the fastener material provides primary support of the front portion across the fault lines. In such embodiments, the fault lines are formed as cut lines of one or more elongate cuts and minor, if any, web connections therebetween, with uncut web portions as the stronger end portions sufficiently strong, in combination, to support integrity of the front portion across the fault lines. The cutting into the fault lines in cutting the leg cut-outs is effective to remove the uncut web portions adjacent the leg cut-outs and to thereby communicate with the cut line,

In some embodiments, the method includes forming the fault lines as cut lines each having one or more elongate cuts and minor, if any, web connections therebetween, with uncut web portions as the relatively stronger end portions of each fault line, and wherein the cutting into the fault lines at cutting of the leg cut-outs comprehends removing the entirety of the relatively stronger uncut web end portions at the respective ends of the fault lines.

In other embodiments, the method includes forming respective such fault lines as cut lines of one or more centrally-disposed elongate cuts and minor, if any, web connections therebetween, with relatively shorter-length perforation cuts and corresponding effective uncut web support connections between such perforation cuts at the relatively stronger ends.

In yet other embodiments, the method includes forming the fault lines as lines of relatively uniform perforations with relatively short and uniform uncut web portions between the respective perforations, and relatively longer uncut web portions at opposing ends of the respective lines of perforations.

In a fourth family of embodiments, the invention comprehends a personal care absorbent article comprising a front portion including an outer front edge and opposing first and second side edges, a rear portion including an outer rear edge, and a crotch portion extending between the front portion and the rear portion. These embodiments also comprise leg openings on opposing sides of the crotch portion, wherein the leg openings can define a first inner end of the front portion and can define a second inner end of the rear portion. Additionally, these embodiments comprise a fastening area disposed on the front portion inwardly of the first and second side edges, and first and second fault lines in the front portion which preclude material of the front portion from independently supporting integrity of the front portion across such fault lines, the respective first and second fault lines being disposed between the fastening area and the respective first and second side edges. These embodiments also comprise first and second fasteners releasably secured to the fastening area, non-releasably secured to the front portion outwardly of the respective fault lines, and unsecured to the front portion between the fastening area and the fault lines.

In some embodiments, the fault lines are cut lines with no front portion material extending across the fault lines.

In other embodiments, the fault lines comprise lines of perforations with limited lengths of front portion material extending across the fault lines.

In preferred embodiments, the fasteners comprise hook-type fasteners engageable with loop material at the fastening area.

5 In a fifth family of embodiments, the invention comprehends a method of manufacturing personal care absorbent articles comprising forming first and second fault lines in the workpiece on opposing sides of the fastening area, wherein the first and second fault lines generally extend substantially from the front edge of the workpiece to the respective leg openings. In such embodiments, the first and second fault lines
10 have points of web-attachment sufficient, in combination, to maintain the integrity of the workpiece as such workpiece proceeds through manufacture.

Each point of web-attachment is generally defined between adjacent cuts and/or perforations on a respective fault line.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1A shows a representative top view of a stream of workpieces indicative of some methods of the invention.

FIGURE 1B shows another representative top view of a stream of workpieces indicative of other methods of the invention.

FIGURE 2A shows an elevated pictorial view of a representative personal care article of methods of FIGURE 1A.

FIGURE 2B shows an elevated pictorial view of a representative personal care article of methods of FIGURE 1B.

FIGURES 3A-3H illustrate exemplary fault line structures.

The invention is not limited in its application to the details of the construction and the arrangement of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments or of being practiced or carried out in various ways. Also, it is to be understood that the terminology and phraseology employed herein is for purpose of description and illustration and should not be regarded as limiting. Like reference numerals are used to indicate like components.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

Referring to FIGURE 1A, the invention comprehends apparatus and methods for assembling personal care absorbent articles. Respective segments of the exemplary illustrated manufacturing process of the invention are indicated by letters "A1-J1".

5 At the segment of the method illustrated at "A1", a stream of workpieces 20 travels along a manufacturing path in the machine direction indicated by directional arrow 76. In the embodiment illustrated in FIGURE 1A, stream of workpieces 20 is defined in the combination of front portion web 26 and rear portion web 28, as well as any other personal care article components employed or affixed, both directly and indirectly, to such webs. At segment "A1" of the process illustrated in FIGURE 1A, strands of elastic 30 are disposed on and/or in front portion web 26. While FIGURE 1A shows elastic strands 30 only at a central portion of the workpiece in segment "A1", it should be understood that such elastic strands are typically spaced along the full widths, and extend along the full lengths, of webs 26 and 28, and that such properties generally carry through to all of process segments "A1-J1".

15 While only front portion web 26 is illustrated comprising elastic 30 in FIGURE 1A, preferred embodiments comprise elastic at least in and/or on portions of one or both of front portion web 26 and rear portion web 28. Other less preferable embodiments comprise no elastic in and/or on one or both front portion web 26 and rear portion web 28. Yet in other embodiments, one or both front portion web 26 and back portion web 28 comprise web materials which demonstrate resiliently stretchable properties such as stretch-bonded laminate materials and neck-bonded laminate materials, as well as other composite elastomeric materials and/or resiliently stretchable materials known to those of ordinary skill in the art.

25 Regardless of the elastic properties selected, manufacture of personal care absorbent articles of the invention is designed and configured such that at least portions, if present, of elastic 30 disposed on and/or in front portion web 26 are generally severed or otherwise deactivated before or during processing of stream of workpieces 20. Yet some embodiments of the invention are designed and configured such that substantially none of the elastic of one or both front portion web 26 or back portion web 28 are deactivated prior to or during the manufacturing process.

Segment "A1" of the process illustrates elastic 30 being severed along a path substantially perpendicular to machine direction 76 at deactivation line 31. Elastic strands disposed on and/or in webs 26, 28 can be deactivated by severing such elastic using e.g. a rotary die cutter, by melt-breaking such elastic using e.g. a heated or ultrasonic function roll, or by any other means known to those skilled in the art for deactivating elastics. In preferred embodiments, deactivation line 31 does not extend closer than about 0.25 inch from either outer edge 55 or inner edge 56 of front portion web 26. Such deactivation deactivates the elastic only at those portions of the respective elastic strands which are not secured to the respective e.g. web 26. Thus, upon severance, the elastic strands, to the extent stretched, and not bonded to the web, retract into a generally unstressed condition. The area over which the elastic strands so retract, suggested by the wavy lines at segment "A1", are thenceforth inactive as far as resilient stretching imparted by the elastics.

At segment "B1" of the manufacturing process, a patch of fastening material 40 comprising landing zone material overlies at least a portion of the area deactivated by the severing of elastics at deactivation line 31, to maintain the integrity of front portion web 26, which tends to be affected by tension forces acting in the machine direction. The patch of landing zone material, comprising a fastening area, can be affixed to front portion web 26 by e.g. applying a suitable adhesive to the landing zone material patch or to the front portion web and affixing the fastening area to front portion web 26 using e.g. a cut-and-place applicator.

The patch of landing zone material comprises a fastening area 40 typically encompassing substantially the entireties of the lengths and the widths of such patch of landing zone material. The patch of landing zone material typically includes a first side 42, a second side 44, a top edge 45, and a bottom edge 46. The first and second sides 42, 44 of the patch of landing zone material are defined in relationship with deactivation line 31. While patch 40 is illustrated as being a one-component, generally rectangular-shaped piece of landing zone material, the fastening area can be defined by a variety of shapes and sizes, and any desired number of separate components. Preferably, patch or patches 40 are designed and configured so as to contribute to the maintenance of the integrity and dimensional stability of front portion web 26 at a portion of deactivation line 31 as a result of the application of the respective fastening patch 40.

Fastening area 40 can be constructed from a material which preferably has e.g. loop properties or hook material properties. In the alternative, any material which can form a cooperative relationship with desired fastener materials, such as those suggested in the discussion of segment "D" of the process, to provide repeatable fastening and releasing properties while maintaining the integrity of front portion web 26, is suitable for use as, or in place of, fastening area 40.

In some embodiments, front portion web 26 comprises a material which demonstrates landing zone properties capable of forming engagement relationships with respective fastener materials defined in step "D" of the process. In such embodiments, step "B1" of the manufacturing process, which includes applying a patch of fastening material 40 to web 26, is not included in the process since at least a portion, and up to the entirety, of the major surface of front web portion 26 already includes fastening area properties.

Therefore, a landing zone may or may not have distinct physical edges, depending on whether the fastening properties desired to be performed thereby (i) are provided by distinct separate e.g. web element(s) or (ii) are integral with a surface of front portion web 26.

At segment "C1" of the manufacturing process, first fault line 32 and second fault line 34 are effected on front portion web 26, both fault lines being effected in a fashion substantially perpendicular to machine direction 76. Fault line 32 is disposed laterally of the most remote portion, with relationship to deactivation line 31, of side 42 of fastening area 40. Similarly, fault line 34 is disposed laterally of the most remote portion, with relationship to deactivation line 31, of side 44 of fastening area 40. As with deactivation line 31, fault lines 32, 34 preferably do not extend closer than 0.25 inch from either outer edge 55 or inner edge 56 of front portion web 26, reserving substantial uncut web portions 38, 39 adjacent outer and inner edges 55, 56. Each respective uncut web portion 38, 39 of front portion web 26 is disposed between an end of a respective fault line and a respective adjacent outer or inner edge 55, 56, respectively, of front portion web 26, wherein substantial uncut web portions 38, 39 comprise support connections which, at least in part, aid in maintaining the integrity of front portion web 26.

In some embodiments, first and second fault lines 32, 34 comprise perforations which can extend effectively to outer edge 55 and/or inner edge 56 of front portion web

26, thus reserving no separately defined substantial uncut web portions 38, 39 adjacent outer and inner edges 55, 56.

As used herein, "substantial uncut web portions" means web portions of significantly greater substance than uncut web portions located between perforations in the same fault line.

"Fault line," as used in the discussion of FIGURE 1A, includes a wide variety of structures which substantially weaken the machine direction strength of the web at the fault line, and can include, for example, a line of perforations, a cut line bounded on opposing ends by perforations, and/or a cut line bounded on opposing ends by uncut material, wherein the length of such cut is at least as great as the length of uncut or un-perforated material at opposing ends of the cut. Other effectively weakening structures will be known to those skilled in the art.

"Fault line perforations" illustrated and referred to herein can take on a variety of configurations. For example and without limitation, such configurations can include straight line slits, curved line slits; lines of multiple straight, curved, or angled slits wherein the slits are aligned with the direction of extension of the fault line; lines of multiple straight, curved, or angled slits wherein the slits are directed at angles to the direction of extension of the fault line. The fault line perforations can also comprise small cut-outs of the material of the front portion web, wherein the cut-outs can have any of a variety of shapes including circular, oval, square, rectangular, other polygonal shapes, star shapes, and the like. Further, the perforations can comprise a combination of the above configurations and shapes.

Fault lines 32, 34 can be effected using a variety of devices including, but not limited to, rotary die cutter, knife cutter, paired rotary horn and anvil, and other faulting means known to those skilled in the art.

Generally, where elastics in an elasticized web are stretched in the machine direction, and the stretched web is severed across the transverse width of the web thus to create a transversely extending free edge, the web tends to retract when such severance takes place. When such severance occurs before e.g. the fastening area material or tab components can be attached, the resulting retraction increases the complexity of making such attachments. Since no such transverse severances are made across elasticized web 26 in the invention, the integrity of the web is maintained while

the fastening area material and fasteners are implemented on the web to, among other functions, assist in maintaining the integrity of the web.

The structure of fault lines 32, 34 can be selected as desired so long as the fault lines are sufficiently strong to tolerate the process segments "C1" and "D1" prior to emplacement of fasteners 66, 68 thereby to reinforce the front portion web across fault lines 32, 34. FIGURES 3A-3H illustrate representative structures for fault lines 32, 34. FIGURE 3A represents a single straight line cut through web 26. FIGURE 3B represents a line of uniformly configured and uniformly spaced perforations. FIGURE 3C represents a single elongate cut and shorter-length perforations at each end of the elongate cut and aligned with the elongate cut. FIGURE 3D represents two aligned elongate cuts and shorter perforations at opposing ends of the fault line. FIGURE 3E represents three elongate cuts, aligned with each other, with the illustrated bridging material between respective ones of the elongate cuts. FIGURE 3F illustrates a fault line wherein the weakness in the fault line is developed by removing small circular bits of web material such that the fault line is represented by an array of cooperating apertures. Such apertures can have a variety of shapes, such as circular, square, rectangular, other polygonal shape, star-shape, and the like. FIGURE 3G illustrates a fault line defined by perforations disposed at an angle to the direction of extension of the fault line. FIGURE 3H illustrates a fault line defined by angled slits directed at angles to the direction of extension of the fault line.

Any of the line structures illustrated or made obvious herein can be effected by forming cuts through the material of web 26. In the alternative, satisfactory fault line structures can be obtained by crushing the material of web 26 in a respective line pattern suitable to develop a desired level of weakness across the respective fault line.

At segment "D1" of the manufacturing process illustrated in FIGURE 1A, first fastener 66 is disposed on front portion web 26 overlying at least a portion of fastening area 40 and extending across first fault line 32. Similarly, second fastener 68 is disposed on front portion web 26 overlying at least a portion of fastening area 40 and extending across second fault line 34. Some embodiments comprise fasteners which effectively span from inner edge 56 to outer edge 55 of front portion web 26, such fasteners preferably being cut and trimmed in a subsequent step of the process.

Referring specifically to second fastener 68 at segment "D1" to define features common to fasteners of the invention, the location of second fastener 68 is such that a floating portion 47 of fastener 68, unattached to either web 26 or fastening area 40, overlies an area of front portion web 26 between second side 44 of fastening area 40 and second fault line 34. The portion of second fastener 68 which overlies a portion of fastening area 40 comprises adjusting portion 49, which, at least in part, cooperatively forms an engagement relationship with fastener receptors in fastening area 40. Base portion 43 of second fastener 68 is disposed at a portion of second fastener 68 most remote from adjusting portion 49. Base portion 43 of second fastener 68 is generally permanently affixed to front portion web 26 remote from fastening area 40 and outside second fault line 34, namely with second fault line 34 between fastening area 40 and base portion 43. Base portions 43 of respective fasteners are affixed to front portion web 26 preferably using adhesive and/or ultrasonic bonding, although other affixation means known to those skilled in the art are contemplated.

Fasteners 66, 68 as illustrated herein define attachment structures which, e.g. in combination with fastening area 40, or the like, can be repeatedly fastened, released, adjusted and re-fastened. Acceptable embodiments of fasteners 66, 68 can include any material capable of forming cooperative engagement relationships with the respective material used for fastening area 40. For example and without limitation, such acceptable fastener materials are adhesives, cohesives, mechanical fasteners such as buttons and corresponding buttonholes, snaps and the like, as well as other fasteners which can be repeatedly fastened and released known to those skilled in the art. Mechanical hook and loop fasteners are preferred because of their associated versatility and cost effectiveness.

At segment "E1" of the manufacturing process, crotch element 60 is attached to front portion web 26 of web sausage 22 at least at or near inner edge 56 of front portion web 26, and to rear portion web 28 of web sausage 22 at least at or near inner edge 59 of rear portion web 28. In the illustrated embodiment, crotch element 60 is attached to surfaces of webs 26, 28 which surfaces are directed away from the viewer. Accordingly, crotch element 60 is shown in dashed outline at the respective webs 26, 28. FIGURE 2A shows crotch element 60 in solid outline.

Crotch element 60 generally comprises absorbent core 74 and leg elastic 69 (FIGURE 2A), although such components can be added to crotch element 60 of web sausage

22 during other portions of the manufacturing process. Crotch element 60 is preferably attached to front portion web 26 and rear portion web 28 via adhesives, although other attachment means known to those skilled in the art are contemplated.

As used herein, "web sausage" includes single and multiple webs, or multiple web elements and components thereof, used as basis or other substrate upon which to build personal care article workpieces. Where multiple webs are used, a second such multiple web can overlie a first such web, or, as illustrated in FIGURE 1A, first and second webs can be advanced in a side-by-side, spaced from each other, arrangement.

At segment "F1" of the manufacturing process, leg cut-outs 36 are separated from front portion web 26 using e.g. a rotary die cutter as indicated by excision arrow 78. The removal of leg cut-outs 36 also disassociates uncut web portions 39 originally disposed at inner edge 56 of front portion web 26, from front portion web 26, thus disabling support connections across fault lines 32, 34 and completing the severance of respective fault lines 32, 34 on first inner edge 56. Separation of the leg cut-outs also develops a preferred edge configuration for crotch element 60 thus to define a crotch portion 63 of FIGURE 2A extending between web 26 and web 28.

At segment "G1" of the manufacturing process, the web sausage is folded at crotch portion 63 such that front portion web 26 and rear portion web 28 are disposed in an overlying relationship with one another wherein respective outer edges 55, 58 of respective webs 26, 28 preferably, but not necessarily, are substantially overlying one another. Such folding of web sausage can be effected using a folding mechanism such as, but not limited to, a helical folder or a folding bar.

At segment "H1" of the manufacturing process, side seam bonds 62 are formed adhering front portion web 26 to rear portion web 28 between adjacent fault lines of respective adjacent individual workpiece precursors 24. Bonds 62 are preferably formed using ultrasonic energy applied by e.g. ultrasonic bonding apparatus. As an alternative to ultrasonic energy, side seam bonds 62 can be implemented using e.g. thermal energy, chemical adhesives, or a combination of chemical adhesives with ultrasonic energy or thermal energy.

At segment "I1" of the manufacturing process, waist trim composite 41 is separated from workpiece precursors 24 using e.g. a slitter apparatus, thus removing a strip of material at and adjacent outer edge 55 of front portion web 26 and any of rear portion web 28 which underlies the removed strip of front portion web 26. The

removal of waist trim composite 41 also disassociates respective uncut web portions 38, originally disposed near respective outer edge 55 of the front portion web, from the front portion web, thus disabling support connections provided by such uncut web portions and completing the severance of the front portion web at respective fault lines 32, 34. Accordingly, once trim composite 41 is removed, fasteners 66, 68 provide primary support of front portion web 26 against machine direction stresses across fault lines 32, 34. Where fault lines 32, 34 represent continuous cut lines cut entirely through the thickness of web 26, fasteners 66, 68 provide all support of the front portion with respect to machine direction stresses across fault lines 32, 34. Where fault lines 32, 34 include support connections or bridges such as uncut areas between perforations elements of a line of perforations, the machine direction support can be shared between such uncut areas and fasteners 66, 68.

At segment "J1" of the manufacturing process, individual workpiece precursors 24 are preferably severed from the web sausage thus to define individual separate and discrete finished personal care products. Such severing can be effected by a cutting in a cross-machine direction along each respective side seam 62 using e.g. a knife and anvil cut-off. Such cut is made between edges 67A, 67B so as to define a bonded such side seam on each of the products so defined by the respective cuts. Such a cut is representatively illustrated as line 80.

Rather than severing or separating individual personal care articles at side seams 62 as illustrated, the respective side seam cut lines can be effected, instead, as lines of weakness such as are illustrated in FIGURES 3A-3H, with complete severance at every "n" workpieces. Such process results in strips of respective personal care articles, each strip containing "n" personal care articles. The strip can then be rolled up for packaging. The user tears a personal care article off the strip for use as desired.

Referring to FIGURE 1B, the invention comprehends yet other embodiments of apparatus and methods for assembling personal care absorbent articles. FIGURE 2B illustrates a personal care absorbent article 50 manufactured from the methods of FIGURE 1B. Respective segments of the exemplary manufacturing process illustrated in FIGURE 1B are indicated by letters "A2-G2".

At the segment of the method illustrated at "A2", a stream of workpieces 20 travels along a manufacturing path in the machine direction indicated by directional

arrow 76. In the embodiment illustrated in FIGURE 1B, stream of workpieces 20 is defined in the combination of front portion web 26 and rear portion web 28, as well as any other personal care article components employed or affixed, both directly and indirectly, to such webs.

5 In some embodiments, one or both front portion web 26 and back portion web 28 comprise web material which demonstrate resiliently stretchable properties such as stretch-bonded laminate material and/or neck-bonded laminate material, as well as other composite elastomeric materials and/or resiliently stretchable materials known to those of ordinary skill in the art. Other embodiments can comprise elastic at least in and/or on portions of one or both of front portion web 26 and rear portion web 28. Other less preferable embodiments comprise little or no elastic in and/or on one or both front portion web 26 and rear portion web 28.

10 Front portion web 26 is preferably constructed from a material which demonstrates landing zone properties capable of forming engagement relationships with respective fastener materials defined in step "D" of the process of FIGURE 1A. In such preferred embodiments, at least a portion, and up to the entirety, of the major surface of front web portion 26 already includes fastening area properties. In other less preferable embodiments of the process illustrated in FIGURE 1B, a patch of landing zone material may be placed on front portion web 26 as demonstrated and described in segment "B1" of FIGURE 1A.

20 Therefore, as with apparatus and methods of FIGURE 1A, apparatus and methods of FIGURE 1B also have a landing zone which may or may not have distinct physical edges, depending on whether the fastening properties desired to be performed thereby (i) are provided by distinct separate e.g. web element(s) or (ii) are integral with a surface of front portion web 26. Thus in any of the embodiments of the invention, a fastening area can be defined in front portion web 26 by applying a separate landing zone patch, by applying a layer of material or coating over front portion web 26 to give it landing zone properties, or by utilizing a material as front portion web 26 which inherently possesses landing zone characteristics.

30 Still referring to segment "A2" of FIGURE 1B, first fault line 32 and second fault line 34 are effected on front portion web 26, both fault lines being effected in a fashion substantially perpendicular to machine direction 76. Fault lines 32, 34 preferably extend completely to outer edge 55 and inner edge 56 of front portion web

26, thereby reserving no substantial uncut web portions adjacent outer and inner edges 55, 56.

5 "Fault line," as used in the discussion of FIGURE 1B, includes a wide variety of structures which weaken the machine direction strength of the web at the fault line but provide sufficient support to maintain the integrity of the web as such web is manipulated during the manufacturing process. A fault line of the methods of FIGURE 1B, unlike the methods of FIGURE 1A, does not have substantial uncut web portions located near/at the inner and/or outer edge of the front portion web. A fault line of FIGURE 1B can include, for example, a line of perforations, a line of segmented/interrupted cuts, a line of a combination of perforations and 10 segmented/interrupted cuts, and/or any other known means of creating a fault line that results in a weakening of the machine direction strength of the web, yet provides sufficient support to maintain the integrity of the web as such web is manipulated during the manufacturing process.

15 As with the methods of FIGURE 1A, the "fault line perforations" of FIGURE 1B can take on a variety of configurations. For example and without limitation, such configurations can include straight line slits, curved line slits; lines of multiple straight, curved, or angled slits wherein the slits are aligned with the direction of extension of the fault line; lines of multiple straight, curved, or angled slits wherein 20 the slits are directed at angles to the direction of extension of the fault line. The fault line perforations of FIGURE 1B can also comprise small cut-outs of the material of the front portion web, wherein the cut-outs can have any of a variety of shapes including circular, oval, square, rectangular, other polygonal shapes, star shapes, and the like. Further, the perforations can comprise a combination of the above 25 configurations and shapes. Any of the line structures illustrated or made obvious herein can be effected by forming cuts through the material of web 26. In the alternative, satisfactory fault line structures can be obtained by crushing the material of web 26 in a respective line pattern suitable to develop a desired level of weakness across the respective fault line.

30 The structure of fault lines 32, 34 can be selected as desired so long as the fault lines are sufficiently strong to tolerate at least process segment "B2" prior to emplacement of fasteners 66, 68 thereby to reinforce front portion web 26 across fault lines 32, 34. In other words, points of web-attachment, in combination, are sufficient

to maintain the integrity and/or uniformity of the web 26 as such web proceeds through the process of manufacture, wherein each point of web-attachment is defined between adjacent cuts and/or perforations on a respective fault line.

At segment "B2" of the manufacturing process illustrated in FIGURE 1B, first fastener 66 is disposed on front portion web 26 extending across first fault line 32. Similarly, second fastener 68 is disposed on front portion web 26 extending across second fault line 34. Some embodiments comprise fasteners which effectively span from inner edge 56 to outer edge 55 of front portion web 26.

Referring specifically to second fastener 68 at segment "B2" to define features common to fasteners of the invention, the location of second fastener 68 is such that a portion of second fastener 68 which overlies a portion of central fastening area 40A comprises adjusting portion 49, which, at least in part, cooperatively forms an engagement relationship with fastener receptors inherent to front portion web 26 in fastening area 40A. Base portion 43 of second fastener 68 is disposed at a portion of second fastener 68 most remote from adjusting portion 49. Base portion 43 of second fastener 68 is generally permanently affixed to peripheral fastening area 40B of front portion web 26 remote from central fastening area 40A and outside second fault line 34, namely with second fault line 34 between central fastening area 40A and base portion 43. Base portions 43 of respective fasteners are affixed to peripheral fastening areas 40B of front portion web 26 preferably using adhesive and/or ultrasonic bonding, although other affixation means known to those skilled in the art are contemplated.

Fasteners 66, 68 as illustrated herein define attachment structures which, e.g. in combination with central fastening area 40A and/or peripheral fastening area 40B, or the like, can be repeatedly fastened, released, adjusted and re-fastened. Acceptable embodiments of fasteners 66, 68 can include any material capable of forming cooperative engagement relationships with the respective material used for fastening areas 40A, 40B. For example and without limitation, such acceptable fastener materials are adhesives, cohesives, mechanical fasteners such as buttons and corresponding buttonholes, snaps and the like, as well as other fasteners which can be repeatedly fastened and released known to those skilled in the art. Mechanical hook and loop fasteners are preferred because of their associated versatility and cost effectiveness.

At segment "C2" of the manufacturing process illustrated in FIGURE 1B, crotch element 60 is attached to front portion web 26 of web sausage 22 at least at or near

inner edge 56 of front portion web 26, and to rear portion web 28 of web sausage 22 at least at or near inner edge 59 of rear portion web 28. In the illustrated embodiment, crotch element 60 is attached to surfaces of webs 26, 28 which surfaces are directed away from the viewer. Accordingly, crotch element 60 is shown in dashed outline at the
 5 respective webs 26, 28. FIGURE 2B shows crotch element 60 in solid outline.

At segment "D2" of the manufacturing process, a leg cut-out, e.g. 36 as in segment F1 of the methods of FIGURE 1A, can be effected as an optional step. Referring to FIGURE 1B, since lines of weakness 32, 34 effectively span the entirety of the cross-machine direction width of front portion web 26, no substantial uncut web portion (39
 10 of FIGURE 1A) need be removed. Thus, step "D2" of the manufacturing process illustrated in FIGURE 1B is included merely to signify that other fabrication steps known to those of ordinary skill in the art, e.g. effecting leg cut-outs, are not essential, but are contemplated in methods of the invention, e.g. for comfort of the wearer and, correspondingly, consumer preference.

At segment "E2" of the manufacturing process illustrated in FIGURE 1B, the web sausage is folded at crotch portion 60 such that front portion web 26 and rear portion web 28 are disposed in an overlying relationship with one another wherein respective outer edges 55, 58 of respective webs 26, 28 are preferably, but not necessarily, substantially overlying one another. Such folding of web sausage can be effected using
 15 a folding mechanism such as, but not limited to, a helical folder or a folding bar.

At segment "F2" of the manufacturing process, side seam bonds 62 are formed adhering front portion web 26 to rear portion web 28 between adjacent fault lines of respective adjacent individual workpiece precursors 24. Bonds 62 are preferably formed using ultrasonic energy applied by e.g. ultrasonic bonding apparatus. As an alternative
 20 to ultrasonic energy, side seam bonds 62 can be implemented using e.g. thermal energy, chemical adhesives, or a combination of chemical adhesives with ultrasonic energy or thermal energy.

At segment "G2" of the manufacturing process, individual workpiece precursors 24 are preferably severed from the web sausage thus to define individual separate and discrete finished personal care products. Such severing can be effected by a cutting
 30 in a cross-machine direction along each respective side seam 62 using e.g. a knife and anvil cut-off. Such cut is made between edges 67A, 67B so as to define a bonded such

side seam on each of the products so defined by the respective cuts. Such a cut is representatively illustrated as line 80.

Rather than severing or separating individual personal care articles at side seams 62 as illustrated, the respective side seam cut lines can be effected, instead, as lines of weakness such as are illustrated in FIGURES 3A-3H, with complete severance at every "n" workpieces. Such process results in strips of respective personal care articles, each strip containing "n" personal care articles. The strip can then be rolled up for packaging. The user tears a personal care article off the strip for use as desired.

10 ~~Sub B~~ In other preferred embodiments of FIGURE 1B, web 26 travel along direction of manufacture 76 on a conveyor, roll, or the like, which maintains the relative positioning of web 26 with respect to such conveyor or roll by e.g. vacuum, suction, static forces, or any other means known in the art for maintaining the relative positioning of a web on a roll or conveyor at least until fasteners 66, 68 are applied to web 26. In such other preferred embodiments of FIGURE 1B, fault lines 32, 34 can comprise any of the above discussed embodiments of fault lines as well as a complete severances across the entirety of web 26. The roll or conveyor used in such embodiments sustains the positioning a respective central fastening area 40A relative to adjacent upstream and downstream peripheral fastening areas 40B, such that fasteners 66, 68 can be applied to such areas of web 26 without unwanted overlap, shifting, or spacing of such areas, relative to each other.

In yet other embodiments, the invention comprehends methods of manufacturing personal care absorbent articles in a format which includes defining a stream of workpieces connected to each other along a web sausage having an indefinite length wherein, instead of webs 26, 28 being two separate webs, personal care articles of the invention are fabricated from at least one single, unitary outer layer web which spans in the cross-machine direction from outer rear edge 58 to outer front edge 55 of FIGURE 1B. In such embodiments, absorbent cores and bodyside liner web, to cover the absorbent cores, can be applied to the stream of workpieces before, during, or after method segments described in FIGURES 1A and 1B. In such unitary-web embodiments, leg cut-outs are mandatory between adjacent workpieces to create a more consumer-accepted e.g. hour-glass configuration of the crotch portion of each resulting personal care article. In such unitary-web embodiments, the implementation of fault lines 32, 34, the application

of fasteners 66, 68, the folding of the stream of workpieces, and the side seam bonding of each respective workpiece are all necessary steps.

Thus, manufacturing processes of the invention achieve novel methods of manufacturing personal care articles by maintaining a stream of workpieces, connected to each other in a web sausage, without severing respective front portions and rear portions from respective front and rear precursor webs until relatively late in the process, with respect to conventional methods, thereby enabling manufacturers of personal care articles to integrate personal care article components into the web sausage in the context of a continuous web of workpieces rather than individual workpiece precursors, while manufacturing a refastable personal care product having separated or effectively weakened fault lines between fastening area 40 and side seams 62. Such methods of the invention result in minimizing waste as well as improving manufacturing efficiency.

Along with methods of manufacture, the present invention also relates to the resultant personal care articles made by such methods of manufacture. While the preferred embodiments of the present invention are described herein in terms of a personal care article such as a pull-on pant or an adult incontinence brief, the invention includes, and is equally applicable to, infant diapers, training pants, and the like.

FIGURES 2A and 2B illustrate personal care articles 50 manufactured using the methods of FIGURES 1A and 1B, respectively. Such personal care articles include a front portion 52 having a central section 61, a first lateral section 51, a second lateral section 53, and a front edge 55, a rear portion 57 having a rear edge 58, and a crotch portion 63. Additionally, personal care article 50 also comprises an absorbent core 74 mounted between a bodyside liner 72 and an outer cover 70. Fastening area 40 is disposed at an outer surface e.g. of central section 61 of front portion 52 and cooperates with first fastener 66 and second fastener 68 in creating a cooperative engagement relationship. Such engagement relationship enables a user to fasten, unfasten and re-fasten fasteners 66, 68 on fastening area 40 thereby to adjust waist sizing of the personal care article. During use, and preferably as packaged, each of the fasteners, e.g. second fastener 68, is releasably secured to fastening area 40 at adjusting portion 49 of the fastener, is non-releasably secured to second lateral section 53 of front portion 52 outwardly of fault line 34 at base portion 43 of the

fastener, and is unsecured to front portion 52 between fastening area 40 and fault line 34 at floating portion 47 of the fastener.

Leg elastics 69 are shown extending generally from the areas peripheral to opposing sides of absorbent core 74, following the contour of the personal care article 50, through crotch portion 63 and ending at or near front portion 52 and rear portion 57. Leg elastics 69 function to gather the material at the side edges of crotch portion 63 along leg openings 64. Leg openings 64 are formed as apertures in the personal care article as front portion 52 is secured to rear portion 57 to form side seams 62 thus to form, as in FIGURES 1A and 1B, personal care articles e.g. as illustrated in FIGURES 2A and 2B, respectively.

Various types of elastic materials are known for use in leg elastics 69. Leg elastics 69 typically provide overall retractive tensions of from about 10 grams to about 400 grams on a given leg opening at stretch-to-stop conditions. Preferably, leg elastics 69 provide tensions of about 50 grams to about 220 grams. More preferably, leg elastics 69 provide tensions of about 80 grams to about 200 grams.

A variety of materials can be employed as webs 26, 28 and/or web sausage 22 components illustrated in FIGURES 1A and 1B, in comprising personal care articles of the invention. Various woven and nonwoven fabrics can be used for bodyside liner 72. For example, bodyside liner 72 can be e.g. a meltblown or spunbonded or other non-woven web of polymeric material selected from the group consisting of polyolefins including polyethylenes and polypropylenes, polyesters, and polyamides, and mixtures, copolymers, and blends of such polymeric fibers. Bodyside liner 72 can also comprise a carded and/or bonded web composed of natural and/or synthetic fibers. The bodyside liner can be composed of a substantially hydrophobic material wherein the hydrophobic material is treated with a surfactant or otherwise processed to impart a desired level of watability and hydrophilicity.

Bodyside liner 72 can comprise nonwoven, spunbonded, polypropylene fabric fabricated with 2.8-3.2 denier fibers, formed into a web having a basis weight of e.g. about 22 grams per square meter and a density of e.g. about 0.06 grams per cubic centimeter. The fabric is preferably surface treated with e.g. about 0.3 weight percent of a surfactant. Bodyside liner 72 typically comprises a fibrous web defining a multiplicity of small e.g. microporous openings randomly spaced between the fibers and according to location and orientation of the fibers, extending from a major surface of

the web into the interior of the web. Such small openings typically extend through the entirety of the thickness of the web.

Addressing structure, bodyside liner 72 can be fabricated using material selected from the group consisting of porous foams, reticulated foams, apertured polymeric films, polymeric fibers, and natural fibers. Bodyside liner 72 can comprise a multiplicity of components or layers which correspond to any of the materials disclosed herein, as well as others known in the art.

It is generally preferred that outer cover 70 of the personal care article be formed from a material which is substantially impermeable to liquids. A typical outer cover 70 can be manufactured from a thin plastic film or other flexible liquid-impermeable material. For example, outer cover 70 can be formed from a film of polymeric material selected from the group consisting of polyolefins including polyethylenes and polypropylenes, polyesters, and polyamides, and mixtures, copolymers, and blends of such polymeric materials, having thicknesses, for example, of from about 0.012 millimeter to about 0.13 millimeter.

In embodiments where outer cover 70 should have a more cloth-like feel, the outer cover can comprise a polyethylene film having a nonwoven web, such as a spunbonded web of polyolefin fibers, bonded to a surface thereof. For example, a polyethylene film having a thickness of about 0.015 millimeter can have thermally or otherwise bonded thereto a spunbonded web of polyolefin fibers having fiber thicknesses of from about 1.5 to about 2.5 denier per filament, which spunbonded web has a basis weight of e.g. about 24 grams per square meter.

Further, outer cover 70 can be formed of a woven or nonwoven fibrous web which has been totally or partially constructed or treated to impart a desired level of liquid impermeability to selected regions which are e.g. adjacent or proximate absorbent core 74.

Still further, outer cover 70 can optionally be composed of a micro-porous material which permits vapors to escape from absorbent core 74 and through outer cover 70 while preventing liquid exudates from passing through the outer cover.

One or both of outer cover 70 and bodyside liner 72 can comprise a fibrous web defining a multiplicity of randomly-spaced small openings extending from a major surface of the web into the interior of the web. Polymeric material such as the recited polyolefins including polyethylenes and polypropylenes, polyesters, and polyamides, and

mixtures, copolymers, and blends of such polymeric materials can be used in either film form or in non-woven fiber form, for one or both of bodyside liner 72 and outer cover 70. As to bodyside liner 72, films are apertured films. As to outer cover 70, fibrous webs are impermeable to e.g. aqueous liquid.

5 Included in the definition of polymeric material above are all routine, common, normal additives known to those skilled in the art of polymeric materials such as processing aids, chemical stabilizers, compatibilizers e.g. where more than one polymer is used, fillers, and the like.

10 Absorbent core 74 suitably comprises hydrophilic fibers, such as a web or matt or loose collection of cellulosic fluff, in combination with a high-absorbency material commonly known as superabsorbent material. Absorbent core 74 preferably comprises a mixture of superabsorbent hydrogel-forming particles and wood pulp fluff. In place of the wood pulp fluff, one can use synthetic, polymeric, meltblown fibers or a combination of meltblown fibers and natural fibers. The superabsorbent material can be
15 substantially homogeneously mixed with the hydrophilic fibers or can be otherwise combined into absorbent core 74.

Alternatively, absorbent core 74 can comprise a laminate of fibrous webs and superabsorbent material or other suitable means of maintaining a superabsorbent material in a localized area. Absorbent core 74 can additionally comprise an un-creped through
20 air dried paper web material known as UCTAD.

Absorbent core 74 can have any of a number of shapes. For example and without limitation, absorbent core 74 can be rectangular, I-shaped or T-shaped. In such products as e.g. refastenable absorbent articles, pants, and the like, absorbent core 74 is preferably narrower in the crotch portion than in the rear portion or the front portion,
25 especially where the crotch portion of the personal care article is narrower than the rear portion or the front portion.

The high-absorbency material in absorbent core 74 can be selected from natural, synthetic and modified natural polymers and materials. The high absorbency material can be inorganic material, such as silica gels, or organic compounds, such as cross-linked polymers. The high absorbency material refers to any structure or composition,
30 along with associated process, which renders normally water-soluble material substantially water insoluble but swellable, whereby absorbent properties are available but the swelled material is substantially immobile after absorbing water-based liquid.

Such superabsorbent material can be fabricated by creating e.g. physical entanglement, crystalline domains, covalent bonds, ionic complexes and associations, hydrophilic associations such as hydrogen bonding, and hydrophobic associations, or Van der Waals forces. Two such superabsorbents are DRYTECH® 2035 M and FAVOR® SXM 880. DRYTECH®
5 available from the Dow Chemical Company, Midland, Michigan. FAVOR® is available from Stockhausen, Inc., Greensboro, North Carolina.

Personal care articles of the invention can be used in at least two different ways. First, personal care article 50 of FIGURES 2A and/or 2B, as shipped to the customer, can be used as a pant-type structure. In such format, first and second
10 fasteners 66, 68, respectively, are, and remain, attached separately to fastening area 40 of front portion 52. The pant-type structure is slipped onto the wearer while retaining attachment of first and second fasteners 66, 68 to fastening area 40 of personal care article 50 through a cooperative engagement relationship.

Accordingly, the legs of the wearer are inserted through waist opening 65, and
15 through leg openings 64. The pant is then pulled in a cephalic direction until leg openings 64 are snugly positioned at the groin of the wearer. The user can adjust the fitting of the pant-type structure to create a better relative positioning of the waist portion of the respective personal care article about the torso of the wearer, directed toward comfort of the wearer, thus to improve the fit.

Further adjusting to obtain a tighter or looser fit can be accomplished by the
20 user by subsequent grasping and pulling of first and/or second fasteners 66, 68, away from fastening area 40, thereby to disengage first and/or second fasteners 66, 68 from fastening area 40. Respective fasteners 66, 68, are then moved over desired locations on fastening area 40 and re-engaged to fastening area 40, so as to achieve the desired
25 relationship between adjusted size of personal care article 50 and size of the wearer. Release and re-fastening of fasteners 66, 68 can occur multiple times, e.g. an indeterminate number of times, to enable proper fitting throughout the expected use life of the personal care article. Fasteners 66, 68 can be adjusted individually or in combination with each other to create a relatively tighter or relatively looser fit.

Preferably, and as a user convenience, personal care articles of the invention
30 are packaged having respective adjustment portions 49 of first and second fasteners 66, 68, cooperatively affixed in an engagement relationship with fastening area 40, whereby

personal care articles of the invention can be mounted on a wearer in a similar fashion to that of conventional pull-on pants.

The second method of using personal care article 50 of FIGURES 2A and/or 2B is to use such article as a diaper-like article. In use as a diaper-like article and before any mounting on the prospective wearer, first and second fasteners 66, 68 are separated from fastening area 40 of personal care article 50, and front portion 52 is pulled away from rear portion 57. In the method of using such article as a diaper-like article, the separation of first and second fasteners 66, 68 from fastening area 40 can be performed before packaging by the manufacturer, or can be performed anytime prior to or during use by the user.

Where fault lines 32, 34 in the personal care article comprise bridging elements of web material bridging across a fault line as in FIGURES 3B-3H, such bridging elements are broken substantially concurrently with separation of fasteners 66, 68 from fastening area 40, thus to completely release lateral sections 51, 53 from central section 61 of the front portion.

After fasteners 66, 68 are separated from fastening area 40, and fault lines 32, 34 are released as necessary, the personal care article is laid on a preferably horizontal surface with bodyside liner 72 facing upwardly. The dorsocaudal portion of the torso of the wearer, e.g. infant or adult, is then laid or otherwise moved onto rear portion 57 of the personal care article. Front portion 52 is then brought frontwardly between the legs of the wearer and onto the torso of the wearer. First and second fasteners 66, 68 are fastened to fastening area 40, completing mounting of the personal care article onto the wearer. Those skilled in the art will recognize the instant above description as a known method of mounting a diaper-like article on a wearer.

Regardless of use as a pull-on pant or diaper-like article, methods of using personal care articles of the invention preferably reflect first and second lateral sections 51, 53 being distinctly defined separate from central section 61 on respective sides of the absorbent article by first and second fault lines 32, 34, respectively, in order for the user to remove a such article without completely removing such user's slacks or outer pants.

Those skilled in the art will now see that certain modifications can be made to the invention herein disclosed with respect to the illustrated embodiments, without departing from the spirit of the instant invention. And while the invention has been

described above with respect to the preferred embodiments, it will be understood that the invention is adapted to numerous rearrangements, modifications, and alterations, all such arrangements, modifications, and alterations are intended to be within the scope of the appended claims.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000